

DIMENSIONS ARE INCHES


Required Utilities:

70 psi Nitrogen – 1/4" Female Pipe Thread (NPT)
 20" Hg Vacuum – 1/4" Female Pipe Thread (NPT)

Bowl Drain – 1" OD Stainless Steel Tube
 Bowl Exhaust – 1 1/2" OD Stainless Steel Tube (20-50cfm)

208-240VAC, 1350W, 7A unless specified

Fuse: 15A Slo-Blow

SCALE	THIRD ANGLE PROJECTION	DESIGN ENGINEER	 Cost Effective Equipment 3703 HyPoint Blvd Rolla, MO 65401 Phone: (573) 466-4300
1: 1		DRAWN BY	
ALL DIMENSIONS ARE BASIC UNLESS OTHERWISE NOTED. LIMITS ON DIMENSIONS ARE	ANGLES ±1°	APPROVED	TITLE
DECIMALS .XX±.015 .XXX±.005 .XXXX±.0005	FRACTIONS ±1/64	DATE	SIZE
THESE DRAWINGS/SPECIFICATIONS ARE THE EXCLUSIVE PROPERTY OF COST EFFECTIVE EQUIPMENT, LLC. THEY SHALL NOT BE REPRODUCED OR COMMUNICATED TO OTHERS, IN WHOLE OR IN PART, NOR BE USED AS A BASIS FOR MANUFACTURE OR SALE OF THE ITEMS REPRESENTED, WITHOUT THE WRITTEN PERMISSION OF COST EFFECTIVE EQUIPMENT, LLC.		3/8/2019	PART NO.
			SHEET
			1 of 1
			CONTROLLER

REVISIONS				
REV	DESCRIPTION	DATE	APPROVED	