


Required Utilities:
 Power: 208-230 VAC, 3669W (16A) max
 Frequency: 50/60 Hz
 35 psi Nitrogen – 1/4" Female pipe thread
 20" Hg Vacuum – 1/4" Female pipe thread
 Bake Plate Exhaust -- 2" OD tube / 5-10 cfm

SCALE	THIRD ANGLE PROJECTION	DESIGN ENGINEER	 Cost Effective Equipment 3703 HyPoint Blvd Rolla, MO 65401 Phone: (573) 466-4300	
1:1		DRAWN BY Jeff Leith		
ALL DIMENSIONS ARE BASIC UNLESS OTHERWISE NOTED. LIMITS ON DIMENSIONS ARE	ANGLES ±1°	APPROVED	TITLE Apogee 300 Bake Plate Utilities	
DECIMALS .XX=±.015 .XXX=±.005 .XXXX=±.0005	FRACTIONS ±1/64	DATE 1/11/2024	SIZE B	PART NO.
THESE DRAWINGS/SPECIFICATIONS ARE THE EXCLUSIVE PROPERTY OF COST EFFECTIVE EQUIPMENT, LLC. THEY SHALL NOT BE REPRODUCED OR COMMUNICATED TO OTHERS, IN WHOLE OR IN PART, NOR BE USED AS A BASIS FOR MANUFACTURE OR SALE OF THE ITEMS REPRESENTED, WITHOUT THE WRITTEN PERMISSION OF COST EFFECTIVE EQUIPMENT, LLC.		MATERIAL	SHEET 1 of 1	CONTROLLER

REVISIONS				
REV	DESCRIPTION	DATE	APPROVED	