



**DIMENSIONS ARE INCHES**

**Required Utilities:**

Power: 100-125VAC, 655W, 50/60 Hz  
 208-240VAC, 655W, 50/60 Hz

70 psi Nitrogen – (N2 only required with auto-dispense)

20" Hg Vacuum – 1/4" Female pipe thread

Bowl Drain – 3/4" OD tube

Bowl Exhaust -- 1" OD tube (20-50cfm)

SCALE	THIRD ANGLE PROJECTION	DESIGN ENGINEER	 Cost Effective Equipment 3703 HyPoint Blvd Rolla, MO 65401 Phone: (573) 466-4300
1: 1		DRAWN BY	
ALL DIMENSIONS ARE BASIC UNLESS OTHERWISE NOTED. LIMITS ON DIMENSIONS ARE	ANGLES ±1°	APPROVED	TITLE
DECIMALS .XX±.015 .XXX±.005 .XXX±.0005	FRACTIONS ±1/64	DATE	Apogee Spinner Utilities
THESE DRAWINGS/SPECIFICATIONS ARE THE EXCLUSIVE PROPERTY OF COST EFFECTIVE EQUIPMENT, LLC. THEY SHALL NOT BE REPRODUCED OR COMMUNICATED TO OTHERS, IN WHOLE OR IN PART, NOR BE USED AS A BASIS FOR MANUFACTURE OR SALE OF THE ITEMS REPRESENTED, WITHOUT THE WRITTEN PERMISSION OF COST EFFECTIVE EQUIPMENT, LLC.		MATERIAL	SIZE
		FINISH	PART NO.
			SHEET
			1 of 1
			CONTROLLER

REVISIONS				
REV	DESCRIPTION	DATE	APPROVED	