

# Apogee™ Mechanical Debonder

With DataStream™ Technology

The Apogee™ debonder enables the use of high temperature bonding materials while maintaining very low-stress room temperature debonding.

*Serving the Semiconductor Industry Since 1987*



## BENEFITS

- Compact design for minimized footprint
- In-house debonding of fully processed thinned device wafers
- Device wafer debonding on film frame to fully support device wafer and minimize handling risk
- Full-color, 7-inch touch screen display
- DataStream™ technology
- Force logging

## TOOL FEATURES & SPECIFICATIONS

- Substrate sizes (round): 50 mm to 300 mm
- Force range: 0 to 100 N (1 to 22 lb)
- Low stress to device wafer
- Excess force sensing: Failsafe error recovery

## PROGRAMMABILITY

- Touch screen interface and display
- Full-color alphanumeric-capable graphical user interface (GUI)
- A virtually unlimited number of user-defined recipe program steps
- 0.1-second resolution for step times (9,999.9 seconds maximum step time)
- View process status and download for offline analysis
- Process traceability for every wafer
- On-line graphical process charts and logs for force and cycle time
- Connectivity: USB/Ethernet port for communications for uploading/downloading process parameters with DataStream™ technology



## RELIABILITY AND THROUGHPUT

Debonding Tool Platform Reliability	
Total Throughput	Up to 20 WPH
Yield	> 98%
Wafer Size	50 mm to 300 mm
Operating Temperature	Room Temperature

## UTILITIES

- Voltage: 110–125, 208–240 VAC; 50/60Hz; Single Phase
- Power: 950 Watts
- Vacuum: <20 kPa (>20 in Hg), 20 liters/min (.7 cfm)
- Nitrogen or CDA: 482.6 kPa (70 psi)

## DIMENSIONS

- 635 mm W x 914 mm D x 1842 mm H  
(25" W x 36" D x 72.5" H)
- Machine weight: 153 kg (337 lb)
- Shipping weight: 300 kg (661 lb)

# DATASTREAM™ TECHNOLOGY: CONNECTING THE SEMICONDUCTOR INDUSTRY

DataStream™ technology gives you access to all of your connected Apogee™ manufacturing equipment in one place to track, access, and modify your systems via a web browser. This technology will give manufacturers the ability to process and visualize data in real time and search and export that data into a number of different formats.

### Real-Time Process Information

- Constant feedback of process information for monitoring critical process parameters
- Streamlined interface between different tool types
- Visual cues on process status & health

### Advanced Recipe Creation

- Seamless switching between basic and advanced recipe creation methods
- Plain-English recipe translation
- Pre-defined process commands
- Unlimited process steps
- Unlimited recipe storage

### Environmental Monitoring

- Monitoring of temperature & humidity allows for stricter control of critical processes
- Set preconditions and tolerances for monitored parameters
- On-screen, colored visual cues for deviation from controlled specs

### Data Logging & Export

- Export data logs into commonly readable formats for further analysis and process troubleshooting
- Increase process efficiency
- Identify process control deviations
- Analyze multiple processes for best known method (BKM) development

© 2019 Cost Effective Equipment, LLC

All statements, technical information, and recommendations contained herein are based on tests we believe to be accurate, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of warranty expressed or implied. Neither the seller nor the manufacturer shall be liable for any injury, loss, or damage, direct or consequential, arising from the use or inability to use the product. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. No statement or recommendation contained herein shall have any force or effect unless in an agreement signed by officers of the seller and manufacturer.

Effective Date: 4/1/2019