


America

CERTIFICATE

No. U8 125057 0001 Rev. 00

Holder of Certificate: **Cost Effective Equipment, LLC**
6 Industrial Drive,
St. James MO 65559
USA

Certification Mark:




Product: **Laboratory Equipment**

This product was voluntarily tested to the relevant safety requirements referenced on this certificate. It can be marked with the certification mark above. The mark must not be altered in any way. This product certification system operated by TÜV SÜD America Inc. most closely resembles system 3 as defined in ISO/IEC 17067. Certification is based on the TÜV SÜD "Testing, Certification, Validation and Verification Regulations (TCVVR)". TÜV SÜD America Inc. is an OSHA recognized NRTL for USA and a Standards Council of Canada ISO/IEC 17065 accredited Certification body for Canada.

Test report no.: 092-72195468-000

Date, 2024-06-06

(Joseph P Janeliunas)



America

CERTIFICATE

No. U8 125057 0001 Rev. 00

Model(s):

Apogee Bake Plate:

A-B-B2-1, A-B-B2-2, A-X-B2-2, A-FP-B2-1, A-FP-B2-2, A-F-B2-1, A-F-B2-2

Apogee 300 Bake Plate

A-B-B3-2, A-X-B3-2, A-F-B3-2

Tested according to:

UL 61010-1:2012/R:2019-07
 UL 61010-2-010:2019
 CSA C22.2 No. 61010-1:2012/A1:2018-11
 CSA C22.2 No. 61010-2-010:2019

Parameters:

Input Voltage:

For Apogee Bake Plate:

100-120Vac / 208-230Vac

For Apogee 300 Bake Plate:

208-230 Vac

Input Frequency:

50/60Hz

Input Current:

For Apogee Bake Plate:

13.3A @ 100-120Vac

6.6A @ 208-230Vac

For Apogee 300 Bake Plate:

16.3A @ 208-230Vac

Input Power:

For Apogee Bake Plate:

1638W @ 100-120Vac

1513W @ 208-230Vac

For Apogee 300 Bake Plate:

3744W @ 208-230Vac

Protection Class:

Class I (PE Connected)

Degree of Protection:


IPX0

Ambient Temperature:

10°C to 30°C

Rated Altitude:

3000 meters



America

CERTIFICATE

No. U8 125057 0001 Rev. 00

Model Name	Mount Style	Size (mm) LxWxH	Weight (kg)	Voltage	Current	Power
A-B-B2-1	Bench Top	510 x 340 x 436	29.26	100-120V	13.3A	1638W
A-B-B2-2	Bench Top	510 x 340 x 436	29.26	208-230V	6.6A	1513W
A-B-B3-2	Bench Top	685 x 477 x 452	66.34	208-230V	16.3A	3744W
A-X-B2-2	X-Pro Mount	510 x 340 x 436	29.26	208-230V	6.6A	1513W
A-X-B3-2	X-Pro Mount	685 x 477 x 452	66.34	208-230V	16.3A	3744W
A-FP-B2-1	Flange with Panels Mount	510 x 340 x 436	29.26	100-120V	13.3A	1638W
A-FP-B2-2	Flange with Panels Mount	510 x 340 x 436	29.26	208-230V	6.6A	1513W
A-F-B2-1	Flange Mount	510 x 340 x 436	29.26	100-120V	13.3A	1638W
A-F-B2-2	Flange Mount	510 x 340 x 436	29.26	208-230V	6.6A	1513W
A-F-B3-2	Flange Mount	685 x 477 x 452	66.34	208-230V	16.3A	3744W